



Swiftpro® K30 Single Sided **Retransfer Card Printer**

KIS Global provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission to revolutionise business identity and access management by building trusted partnerships through our simple SMART™ partner distribution networks.

The Swiftpro K30 retransfer card printer has an outstanding print quality for single-sided printing. With 300dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K30 printer is available with contact and contactless smart code encoding technologies and 100 cards input and output hopper with optional 250 hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important, more important is ensuring the supply of Genuine Swiftpro Supplies and Retransfer film is also critical in delivering reliability, print quality and vibrant colours for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorised Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 300 dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.




INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



Swiftpro® K30 Single Sided

Retransfer Card Printer



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

Printing

Dye Sublimation Retransfer
Full Color Retransfer printing
Single Sided Printing
Up to 130 Cards Per Hour
256 Graduation Printing
Over the Edge Printing on CR80, ID-1 Cards

Standard Features

USB & Ethernet connectivity
100 Input Hopper (30mil)
100 Output Hopper (30mil)
LCD Panel
300 DPI Print Resolution
36 Month Printer Warranty
Lifetime Printhead Warranty
Microsoft Certified Drivers
Solenoid Electronic Locks for Input Hopper
Solenoid Electronic Locks for Supplies / Front Door Housing
Controlling Lock/Unlock from Status Monitor
K Ribbon Erase Function
IpSec Security for Secure Data Encryption IPv6 and IPv4
Inline Bend Remedy
MAC Address Forced Printing (UV Panel on Card)
Kensington Locks

Encoding

Contactless Encoder, Omnikey 5127 (iClass, Mifare and Desfire)
Contact Encoder (CF-7CRW / Control board)
Contact Encoder (CF-7CCS / IC Contact Station)

Software Supported

CardPresso
Card Exchange
All Card Personalisations software used through Swiftpro Driver*
*check with Software vendor and some feature may be limited for use on Swiftpro Printers
Microsoft® Windows® 7, 8, 10 32bit / 64bit
Microsoft® Windows® Server 2008 R2 (SP1) 64bit
Microsoft® Windows® XP Server 2012 64bit

Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield
YMCKP Peel Off Ribbon - 750 Yield
YMCKU UV - 750 - Yield
InTM Retransfer Film - 1000 Yield

Physical Specification

Height	335mm	Without Card Stacker
Width	343mm	Without Card Stacker
Depth	322mm	Without Card Stacker
Weight	13.5 KG	

Interface

USB2.0 (Hi-speed / Full Speed)
Ethernet (100BASE-TX / 10BASE-T)

Options

Flipper Unit

Electrical

Temperature: 15°C to 30°C
Humidity: 35% to 70% (YMCK ink, No Condensation)
3.5A (100V system) 1.6A (220V system)
310W (maximum power when all options are installed)

Card Specification

Card Thickness 10-40mil
Card Size ISO 7810 Format, CR80, ID-1
Card Material: PVC, PC, PET, PET-G
Technology Cards Contact and or Contactless with and Without Mag Stripe



KIS Global GmbH
Oststrasse 34, Duesseldorf Germany 40211
T: +49-211-3689-255 E: channel@kisglobal.com
www.kisglobal.com



Pioneering SMART™ Business Operations